

DATA SHEET SSS-87P

Solid State Loadswitch:

Description:

The PDC SSS-87 Loadswitch series is a tri-pack, modular, solid state relay designed specifically to meet NEMA specifications, as well as California and New York "Model 200" specifications. Each loadswitch contains 3 individually replaceable modules that are enclosed in a dust resistant, metal enclosure providing mechanical protection and excellent heat sinking for the modules. Each module is encapsulated in epoxy resin. The modules are easily accessible with the use of a screwdriver.

Installation:

The switchpac inter mates with any standard NEMA loadbay or with the model 332 cabinet output file as well as with any NEMA loadbay. It is easily installed or removed by grasping the handle. Connector P1 pin outs are shown in FIG 1. The connector mates with a PDC BCS-12 or equal.

the

connector i	mates with a PDC BCS-12 or equal.	
PIN	FUNCTION	P1
1	+115VAC, 60 Hz	(P1 as viewed from the outside of the product looking directly at t
connector)		
2	Chassis Ground	
3	A Output (Red, Don't Walk)	
		2 1
4	Not Assigned	
5	B Output (Yellow)	4 3
6	A Input (Red, Don't Walk)	1 6 ■ 5
7	C Output (Green, Walk)	
8	B Input (Yellow)	8 7
9	+24 VDC	
10	C Input (Green, Walk)	10 9
11	Not Assigned	12 11
12	Not Assigned	
		EIC 1

FIG 1.

General Characteristics:

Model	SSS-87 Series	
Uses Module #	SSR-83-525 & SSR-87	
Meets Specs for	Nema, Caltrans, NY (model 200)	
Load	voltage120 VAC	
	current (max)	
Control Signal	voltage+24VDC	
•	current	
Switching	1st alternation after±10 Degrees of line voltage at the zero	
•	signal is applied. crossover point.	
	Succeeding alterations±5 Degrees of line voltage at the zero crossover point.	
Off State	dv/dt100 V per microsecond	
	line to load resistance15 K Ohms Min	
	leakage currentless than 20 MA	
Isolation	voltage2500 VDC Min	
	resistance10 Meg Ohms Min	
Surge Current	one cycle175 Amps RMS Min	
_	one second40 Amps RMS Min	
Life	operations30 million Min	
Mechanical	lenght8.40 inches	
	width1.74 inches	
	height4.185 inches	
	weight1.135 LBS	

Guarantee: The SSS-87 series is fully guaranteed against all failures due to manufacturing defects for two years.